FOTON AUMAN EST-M

SERIES II

NEW ZEALAND'S ONLY MEDIUM DUTY TRUCK POWERED BY CUMMINS











MAKE & MODEL	
Make Model	FOTON Auman EST-M (BJ1126)
ENGINE	
Supplier Model	CUMMINS ISF4.5-S5185
urbocharger	Yes (with Intercooler)
Rated Power (kW)	157 (210hp)
Rated Torque (Nm)	760
Emission Standard	Euro 5
Emission Control	CUMMINS AdBlue
AIR INTAKE	
Supplier System	CUMMINS Integrated High Position Intake
Air Filters	Primary & Secondary
FUEL	
Supplier System	BOSCH Common Rail Direct Injection
	200
Fank Capacity (L) Fank Material	
	Alloy
Filtration System	CUMMINS
ELECTRICAL	
System Voltage (V)	24
Alternator Capacity (V / A)	28 / 70
Batteries (V)	2 x 12 (135Ah) with Isolating Switch
Headlamp Type	Integrated Halogen with LED DRL
Fog Lamp	Yes (Front & Rear)
Starter Motor (kW)	3.6
CAN Bus Technology	Yes
TRANSMISSION	
Supplier Version	ZF Ecolite 6S1000 (MT)
Gears	6 Speed
Drive Type	4 X 2
PTO Provision	Yes (Rear of Gearbox)
Gear Ratios (:1)	1st: 6.750 2nd: 3.600 3rd: 2.130 4th: 1.39
	5 th : 1.000 6 th : 0.780 Rev: 6.060
CLUTCH	
Operation	Single Disc, Dry Type, Diaphragm Spring
System	Hydraulic
Diametre (mm)	395
CHASSIS	
Гуре	Longitudinal Beam High Strength Steel
Pre-Drilled	Yes
STEERING	
	B. J. J. B. B. C. J. S.
Operation	Recirculating Ball Steering Gear
Type	Power Assisted
Furning Circle (m)	17
Steering Column	2-Way Adjustable
Steering Wheel Controls	Audio, Bluetooth & Cruise Control
SUSPENSION	
Front Suspension Type	Multi Leaf Spring
Rear Suspension Type	Multi Leaf Spring with Helper Spring
Stabiliser Bar	Yes (Front & Rear)
Shock Absorbers	Yes (Double Acting)
BRAKES	
Brake System	Dual Circuit Air Brake
Brake Type	Drum (Front & Rear)
Anti-Lock Brake System (ABS)	Yes
Traction Control System (ASR)	Yes
	Yes
Hill Assist Start (HAS)	Yes
Syhaust Brako	
Exhaust Brake	
Exhaust Brake Parking Brake (with Alarm) Air Junction Terminal	Energy Storage Spring Air Brake Yes

Front Aulo Tun-	Company of Decision
Front Axle Type	Connected I-Beam
Rear Axle Type Axle Max. Capacities (kg)	Full Floating Banjo (Stamped & Welded Housing)
Rear Axle Ratio	5450 (Front) 9000 (Rear)
WHEEL & TYRE	
Tyres	265/70 R19.5
No. of Studs	8
INTERIOR & CAB	
Cab Type	Forward Control Hydraulic Power 55° Tilt
Cab Structure	ECE-29 European Cab Strength Approved
Seating Capacity	2
Front Opening Mask	Yes
Information Centre	Yes (Multi-Display)
Heating & Air Conditioning	Yes
Driver's Seat	Air Sprung, 8-Way Adjustable
Adjustable Steering Wheel	Yes (Telescopic & Tilt)
Central Locking	Yes (Remote)
Powered Windows Reverse Camera	Yes
Cruise Control	Yes
MP5 / WMA / Radio Audio	Yes (7 x 5" screen)
Bluetooth Capability	Yes (Hands-free)
Storage	Centre Console, Overhead, Glove Box, Door Pockets
Cup Holders	2
Roof Mounted Clearance Lights	Yes (LED)
Power Outlets	2
Step Lighting	Yes (Driver & Passenger)
Exterior Mirrors	4 (Power Adjustable, Heated)
Daytime Running Lights	Yes (LED)
Safe Start™	Yes
Parkbrake Alarm	Yes
VEHICLE MASSES 1	
Kerb Weight (kg) ²	4020
GVM (kg)	12000
Max Load (kg) - Body + Payload	7820
GCM (kg)	20000
Max. Tow Rating (kg)	8000
Axle Tare Masses (kg)	2500 (Front) 1520 (Rear)
Gross Axle Mass Capacities (kg)	5450 (Front) 9000 (Rear)
Axle Loading Limits (kg)	5450 (Front) 8200 (Rear)
Tyre Capacities (kg)	5450 (Front) 9440 (Rear)
DIMENSIONS	
Wheelbase (mm)	4500
Overall Dim - LxWxH (mm) ³	7800 x 2550 x 3620
Wheel Track (mm)	1922 (Front) 1800 (Rear)
Overhang - Cab Chassis (mm)	1270 (Front) 2030 (Rear)
Chassis Width (mm)	940 (Front) 865 (Rear)
Rear Axle Width (mm)	2403
Rear End Height (mm)	921
Ground Clearance - Loaded (mm)	235
Cab to Chassis End (mm)	6083 4053
Cab to Axle (mm) Minimum Body Gap (mm)	4053 83
WARRANTY 4	
Duration (whichever occurs first)	3 Years or 200,000 km
OPTIONS & ACCESSORIE	s
Air Deflector	Optional
Seat Covers	Optional
	Optional
Metallic Paint	
Metallic Paint Exterior Sunvisor	Optional
	Optional Optional

- Vehicle load ratings and max. axle capacities may be limited by local laws. Always refer to NZTA's latest regulations when confirming load restrictions and license class requirements for your vehicle.
 Kerb weight is approximate only and includes the weight of the vehicle with fuel and spare wheel.
 Overall dimensions are taken from an original, unladen cab chassis and excludes side mirrors.
 The manufacturer's warranty of 3 Years or 200,000km applies to the Cab & Chassis of new vehicles only. The warranty period for the manufacturer's Job Ready™ body on a new vehicle is 12 months.