FOTON AUMARK S

NEW ZEALAND'S ONLY LIGHT DUTY TRUCK POWERED BY CUMMINS

BJ1065 CHILLER



FOTON DNA:









Make	FOTON
Model	Aumark S - BJ1065
ENGINE	
Supplier Version Displace.	CUMMINS F 2.5L
Turbocharger	Yes (with Intercooler)
Rated Power (kW)	110 @ 2900rpm
Rated Torque (Nm)	400 @ 1500-2900rpm
Emission Standard	Euro 6
Emission Control	AdBlue (SCR+DOC+DPF)
FUEL	
Supplier System	BOSCH Common Rail Direct Injection
Tank Capacity	80L
Tank Material	Alloy
ELECTRICAL	3
System Voltage (V)	24
Batteries (V)	2 x 12 (100Ah)
CAN Bus Technology	Yes
EBP (Fuel Saving Switch)	Yes
LIGHTING	
Headlamp Type	Integrated Halogen (LED DRL)
Adjustable Headlights	Yes
Fog Lamps	Yes (Front & Rear)
Daytime Running Lights	Yes (LED)
Roof Clearance Lights	Yes (LED)
Step Lighting	Yes (Driver & Passenger)
Side-turn Light with Corner Lamp	Yes
TRANSMISSION	
Supplier Version	ZF 5S408 (MT)
Gears	5 Speed
Drive Type	4x2
PTO Provision	Yes (LHS of Gearbox)
Gear Ratios (:1)	1 st : 5.762 2 nd : 2.922 3 rd : 1.638 4 th : 1.00
()	5 th : 0.782 Rev: 5.149
CLUTCH	
Operation	Single Disc, Dry Type Diaphragm Spring
System	Air Boost
Diameter (mm)	325
CHASSIS	
Туре	Longitudinal Beam High Strength Steel
Side Rail Dimensions (mm)	180 x 65 x 4.5
STEERING	
Operation	Closed Recirculating Ball Steering Gear
Туре	Hydraulic Boost
Steering Column	2-Way Adjustable
Steering Wheel Controls	Audio / Bluetooth / Cruise Control
SUSPENSION	
Suspension Type - Front	Multi Leaf Spring
- Rear	Multi Leaf Spring with Helper Spring
Shock Absorbers	Hydraulic 2-way
Stabiliser Bar	Yes
BRAKES	
Supplier System	WABCO Air Brake
Brake Type	Disc (Front) Drum (Rear)
Anti-Lock Brakes (ABS)	Yes
Traction Control (ASR)	Yes
Electronic Stabilisers (ESP)	Yes
Hill Start Assist (HSA)	Yes

Exhaust Brake WHEEL & TYRE Tyre Size No. of Studs AXLES 3 Axle Type - Front - Rear Axle Type - Front - Rear Axle Max. Capacities (kg) Rear Axle Ratio A3: 1 INTERIOR & CAB Cab Type Cab Structure Door Impact Beam Stamped Beam Yes Seating Capacity 3 Heating & Air Conditioning Yes Seating Capacity Tyes Central Locking Power Windows Crulse Control Bluetooth Capability Yes (Touch Screen) Bluetooth Capability Yes Storage Cup Holders Power Outlets Exterior Mirrors Exterior Mirrors Exterior Mirrors Reverse Sensors 1 Reverse Sensors 1 Not on Chiller (kg) Ayes Control City Reverse Alarm Yes Power Weight - Chiller (kg) Ayes Control City Reverse Alarm Yes Power Weight - Chiller (kg) Ayes Control City Ayes Reverse Length (mm) Doverall Dim - LxWxH (mm) 4 Blue (front) 1940 (Rear) Blue (front) 1940 (Rear) Ayes Revergeration Unit Thermo King RV380 Tyes Power Outlets Ayes Revigeration Unit Thermo King RV380 Tyes (Remote) Power Notes (Remote) Power Notes (Remote) Power Adjustable A Heate Lane Departure Warning Ayes Reverse Langth (mm) Ayes Power Outlets Ayes Reverse Langth (mm) Ayes Ayes Reverse Alarm Yes Power Outlets Ayes Reverse Alarm Yes Power Outlets Ayes Reverse Alarm Yes Power Windows Ayes Reverse Alarm Yes Ayes Reverse Alarm Yes Power Windows Ayes Reverse Alarm Yes Ayes Reverse Alarm Yes Power Windows Ayes Reverse A	Air Tank Material	Alloy (x2)
Tyre Size	Exhaust Brake	*
Tyre Size	WHFFL & TYRF	
No. of Studes AXLES 3		205/75R16
AxLES 3 Axle Type - Front	<u> </u>	
Axle Type - Front Forged & Stamped Leam Rear Stamped & Welded Banjo Axle Max. Capacities (kg) 2640 (Front) 4950 (Rear) Rear Axle Ratio 4.3:1 INTERIOR & CAB Cab Type Single Cab Forward Control Till (4 Cab Structure ECE-R29 European Cab Strength App Door Impact Beam Yes Seating Capacity 3 Heating & Air Conditioning Yes Steering Wheel Collapsible/Adjustable (Telescopic & Central Locking Power Windows Yes (Remote) Power Windows Yes (Remote) Power Modulos Yes (Remote) Power Modulos Yes (Remote) Power Mindows Yes Cruise Control Yes (Remote) MPS / WMA / Radio Audio Yes (Touch Screen) Bluetooth Capability Yes (Hands-free) Storage Centree Console, Overhead Locke Glove Box & Door Pockets Cup Holders Yes Power Outlets 2 x Port 2 x USB Exterior Mirrors 5 (2 x Power Adjustable Action Box Dockets Screen) Exterior Mirror		5
Rear		Forged & Stamped I Ream
Axle Max. Capacities (kg) 2640 (Front) 4950 (Rear) Rear Axle Ratio 4.3:1 INTERIOR & CAB 4.3:1 Cab Structure ECE-R29 European Cab Strength App. Door Impact Beam Yes Seating Capacity 4.6 Heating & Air Conditioning Yes Steering Wheel Collapsible/Adjustable (Telescopic & Central Locking Power Windows Yes Cruise Control Yes (Remote) MP5 / WMA / Radio Audio Yes (Touch Screen) Bluetooth Capability Yes (Hands-free) Storage Centre Console, Overhead Locke Glove Box & Door Pockets Cup Holders Yes Power Outlets 2 x Port 2 x USB Exterior Mirrors 5 (2 x Power Adjustable & Heate Lane Departure Warning Yes Reverse Camera Yes Reverse Sensors 1 Not on Chiller Body Reverse Sensors 2 Not on Chiller Body Reverse Alarm Yes VEHICLE MASSES 3 Yes Kerb Weight - Chiller (kg) 2795 GCM (kg) 3500	**	
Rear Axle Ratio 4.3:1 INTERIOR & CAB Cab Type Single Cab Forward Control Tilt (4 Cab Structure ECE-R29 European Cab Strength App Door Impact Beam Yes Seating Capacity 3 Heating & Air Conditioning Yes Steering Wheel Collapsible/Adjustable (Telescopic & Control Coking Power Windows Yes Cuise Control Yes MP5 / WMA / Radio Audio Yes (Touch Screen) Bluetooth Capability Yes (Hands-free) Storage Centre Console, Overhead Lock Glove Box & Door Pockets Cup Holders Yes Power Outlets 2 x Port 2 x USB Exterior Mirrors 5 (2 x Power Adjustable & Heate Lane Departure Warning Yes Reverse Camera Yes Reverse Sensors 1 Not on Chiller Body Reverse Alarm Yes VEHICLE MASSES 3 Kerb Weight - Chiller (kg) 2 3200 GVM (kg) 5995 Max Payload - Chiller (kg) 2795 GCM (kg) 9495 <		
NTERIOR & CAB		
Cab Type Single Cab Forward Control Tilt (4 Cab Structure ECE-R29 European Cab Strength App Door Impact Beam Yes Seating Capacity 3 Heating & Air Conditioning Yes Steering Wheel Collapsible/Adjustable (Telescopic & Central Locking Yes (Control Locking Yes (Control Control Control Control Control Control Control Control Yes (Touch Screen) Bluetooth Capability Yes (Hands-free) Storage Centre Console, Overhead Locke Glove Box & Door Pockets Cup Holders Yes Power Outlets 2 x Port 2 x USB Exterior Mirrors 5 (2 x Power Adjustable & Heate Lane Departure Warning Yes Reverse Camera Yes Reverse Camera Yes Reverse Alarm Yes VEHICLE MASSES Kerb Weight - Chiller (kg) 2 3200 GVM (kg) 5995 Max Payload - Chiller (kg) 2 3200 GVM (kg) 4995 Max Payload - Chiller (kg) 2 3200 GVM (kg) 3500 DIMENSIONS Wheelbase Length (mm) 2800 Overall Dim - LxWxH (mm) 4 5400 x 1925 x 2230 Min Ground Clearance (mm) 175 BODY Inner Dimensions - LxWWH 3430 x 2080 x 1920 Refrigeration Unit Thermo King RV380 Insulation Thickness (mm) 90 (Walls) 110 (Floor) Flooring Alloy with Side Protection Panel Door Access 1 x Single (LHS) & 1 x Double (Rec Stainless Steel Locking Bars Stide Step Yes (Retractable) Cargo Control Racks 3 x Stainless Steel Tri Track Row Tail Lift Activation Cordless Remote & Foot Control Tail Lift Activation Yes WARRANTY Cab & Chassis 3 Year or 160,000km		4.3:1
Cab Structure ECE-R29 European Cab Strength Apr Door Impact Beam Yes Seating Capacity 3 Heating & Air Conditioning Yes Steering Wheel Collapsible/Adjustable (Telescopic & Central Locking Power Windows Yes Cruise Control Yes MP5 / WMA / Radio Audio Yes (Touch Screen) Bluetooth Capability Yes (Hands-free) Cup Holders Yes Power Outlets 2 x Port 2 x USB Exterior Mirrors 5 (2 x Power Adjustable & Heate Lane Departure Warning Yes Reverse Camera Yes Reverse Sensors 1 Not on Chiller Body Reverse Alarm Yes VEHICLE MASSES 3 Yes Kerb Weight - Chiller (kg) 2 3200 GVM (kg) 5995 Max Payload - Chiller (kg) 2795 GCM (kg) 9495 Max Tow Rating (kg) 3500 DIMENSIONS Wheel Track (mm) 2800 Wheel Track (mm) 1820 (Front) 1940 (Rear) Wheel Track		C'
Door Impact Beam Yes Seating Capacity Heating & Air Conditioning Yes Steering Wheel Collapsible/Adjustable (Telescopic & Central Locking Power Windows Cruise Control MP5 / WMA / Radio Audio Bluetooth Capability Yes (Hands-free) Storage Centre Console, Overhead Locke Glove Box & Door Pockets Cup Holders Power Outlets Exterior Mirrors Capacity Fes Ference Camera Yes Reverse Camera Reverse Sensors Not on Chiller Body Reverse Alarm Yes VEHICLE MASSES Kerb Weight - Chiller (kg) GCM (kg) Max Payload - Chiller (kg) DIMENSIONS Wheel Dase Length (mm) Overall Dim - LxWxH (mm) Min. Ground Clearance (mm) BODY Inner Dimensions - LxWxH Refrigeration Unit Thermo King RV380 Tail Lift Activation Tail Lift Activation Tail Lift Activation Tes Vers Collapsible/Adjustable (Telescopic & Search) Yes Collapsible/Adjustable (Telescopic & Search) Yes Centre Console, Overhead Locke Glove Box & Door Pockets Centre Console, Overhead Locke Glove Box & Door Pockets Search 2 x Ver 2 x USB Exterior Mirrors Yes Yes Power Outlets 2 x Port 2 x USB 5 (2 x Power Adjustable & Heate 2 x Port 2 x USB 5 (2 x Power Adjustable & Heate 2 x Port 2 x USB 5 (2 x Power Adjustable & Heate 2 x Port 2 x USB 5 (2 x Power Adjustable & Heate 2 x Port 2 x USB 5 (2 x Power Adjustable & Heate 2 x Port 2 x USB 5 (2 x Power Adjustable & Heate 1 x Single Body 1 x Single (HS) Tail Lift Activation Cordless Remote & Foot Control Tail Lift Activation Tail Lift Activation Cordless Remote & Foot Control Tail Lift Roll Stop Yes VARRANTY Cab & Chassis 3 Year or 160,000km	**	
Seating Capacity Heating & Air Conditioning Steering Wheel Collapsible/Adjustable (Telescopic & Central Locking Power Windows Yes Cruise Control WFS / WMA / Radio Audio Bluetooth Capability Yes (Hands-free) Storage Centre Console, Overhead Locker Glove Box & Door Pockets Cup Holders Power Outlets Yes Power Outlets Sterior Mirrors Sterior Mirrors Sterior Mirrors Sterior Mirrors Sterior Sensors Not on Chiller Body Reverse Sensors Reverse Sensors Reverse Sensors Reverse Alarm Yes Yes WFHICLE MASSES Kerb Weight - Chiller (kg) GCM (kg) Max Payload - Chiller (kg) GCM (kg) Max. Tow Rating (kg) DIMENSIONS Wheel Brack (mm) Min. Ground Clearance (mm) BODY Inner Dimensions - LxWxH Refrigeration Unit Insulation Thickness (mm) Poor Access Side Step Yes (Retractable) Cargo Control Racks Side Step Yes WARANTY Cab & Chassis 3 Year or 160,000km		
Heating & Air Conditioning Steering Wheel Collapsible/Adjustable (Telescopic & Central Locking Power Windows Cruise Control Wes MP5 / WMA / Radio Audio Bluetooth Capability Storage Centre Console, Overhead Locke Glove Box & Door Pockets Cup Holders Power Outlets Exterior Mirrors Lane Departure Warning Reverse Camera Reverse Sensors¹ Not on Chiller Body Yes (Yes WEHICLE MASSES³ Kerb Weight - Chiller (kg) GCM (kg) DIMENSIONS Wheel Brack (mm) Win. Ground Clearance (mm) BODY Inner Dimensions - LXWXH Refrigeration Unit Insulation Thickness (mm) Tail Lift Activation Tail Lift Activation Cordless Remote Posses (Poss) Yes Centre Console, Overhead Locke Glove Box & Door Pockets Yes (Hands-free) Centre Console, Overhead Locke Glove Box & Door Pockets Yes (Passes) Yes (Passes) Yes (Passes) Yes (Passes) Yes Centre Console, Overhead Locke Glove Box & Door Pockets Yes (Passes) Yes (Pas	·	
Steering Wheel Central Locking Power Windows Cruise Control Wes MP5 / WMA / Radio Audio Bluetooth Capability Yes (Hands-free) Storage Centre Console, Overhead Locke Glove Box & Door Pockets Cup Holders Power Outlets Cup Holders Power Outlets Sterior Mirrors Severse Camera Reverse Sensors Reverse Sensors Reverse Alarm VEHICLE MASSES Kerb Weight - Chiller (kg) GCM (kg) Max Payload - Chiller (kg) Max Tow Rating (kg) DIMENSIONS Wheelbase Length (mm) Overall Dim - LxWxH (mm) Min. Ground Clearance (mm) BODY Inner Dimensions - LxWxH Refigeration Unit Insulation Thickness (mm) Poor Access Cintre Console, Overhead Locke Glove Box & Door Pockets Yes (Hands-free) Centre Console, Overhead Locke Glove Box & Door Pockets Yes (Hands-free) Centre Console, Overhead Locke Glove Box & Door Pockets Steverse Camera Yes Ves Ves Power Outlets Steverse Alarm Yes Ves Ves Ves Ves Ves Ves Ves Ves Ves V		
Central Locking Yes (Remote) Power Windows Cruise Control WPs MP5 / WMA / Radio Audio Bluetooth Capability Yes (Hands-free) Centre Console, Overhead Locke Glove Box & Door Pockets Cup Holders Yes Power Outlets Yes Power Outlets 2 x Port 2 x USB Exterior Mirrors 5 (2 x Power Adjustable & Heate Lane Departure Warning Reverse Camera Reverse Sensors¹ Not on Chiller Body Reverse Alarm Yes VEHICLE MASSES³ Kerb Weight - Chiller (kg)² GVM (kg) Sp95 Max Payload - Chiller (kg) GCM (kg) Max. Tow Rating (kg) DIMENSIONS Wheelbase Length (mm) Overall Dim - LxWXH (mm)⁴ Wheel Track (mm) BODY Inner Dimensions - LxWXH Refrigeration Unit Insulation Thickness (mm) Poor Access I al Single (LHS) & 1 x Double (Rea Door Locks Stainless Steel Locking Bars Side Step Yes (Retractable) Yes WARRANTY Cab & Chassis 3 Year or 160,000km	Heating & Air Conditioning	
Power Windows Cruise Control MP5 / WMA / Radio Audio Bluetooth Capability Yes (Hands-free) Storage Centre Console, Overhead Locke Glove Box & Door Pockets Cup Holders Power Outlets Yes Power Outlets 2 x Port 2 x USB Exterior Mirrors 5 (2 x Power Adjustable & Heate Lane Departure Warning Reverse Camera Reverse Sensors 1 Not on Chiller Body Reverse Alarm Yes VEHICLE MASSES 3 Kerb Weight - Chiller (kg) 2 GVM (kg) Fogo Max Payload - Chiller (kg) Fogo Max Tow Rating (kg) DIMENSIONS Wheelbase Length (mm) Overall Dim - LxWxH (mm) 4 S400 x 1925 x 2230 Wheel Track (mm) Min. Ground Clearance (mm) BODY Inner Dimensions - LxWxH Refrigeration Unit Thermo King RV380 Dor Locks Stainless Steel Locking Bars Side Step Cargo Control Racks Tail Lift Tail Lift Activation Tail Lift Activation Togol Warn Pyes Ves Centre Console, Overhead Locke Glove Refroenal Locke Glove Powerhead Locke Glove Powerhead Locke Glove Power (Just) Yes Centre Console, Overhead Locke Glove Power (Just) Yes Centre Console, Senente & Foot Control Tail Lift Activation Togology Cordon Yes VARRANTY Cab & Chassis 3 Year or 160,000km	Steering Wheel	Collapsible/Adjustable (Telescopic & Tilt)
Cruise Control MP5 / WMA / Radio Audio Bluetooth Capability Storage Centre Console, Overhead Locke Glove Box & Door Pockets Cup Holders Power Outlets Exterior Mirrors Exterior Mirror Exte	Central Locking	Yes (Remote)
MP5 / WMA / Radio Audio Bluetooth Capability Yes (Hands-free) Centre Console, Overhead Locke Glove Box & Door Pockets Cup Holders Power Outlets 2 x Port 2 x USB Exterior Mirrors 5 (2 x Power Adjustable & Heate Lane Departure Warning Reverse Camera Reverse Sensors¹ Not on Chiller Body Yes VEHICLE MASSES³ Kerb Weight - Chiller (kg)² GVM (kg) 5995 Max Payload - Chiller (kg) GCM (kg) Max Payload - Chiller (kg) Max Payloa	Power Windows	Yes
Bluetooth Capability Yes (Hands-free) Centre Console, Overhead Locke Glove Box & Door Pockets Cup Holders Yes Power Outlets Exterior Mirrors Exterior Mirrors Reverse Camera Reverse Sensors 1 Kerb Weight - Chiller (kg) GCM (kg) Max Payload - Chiller (kg) DIMENSIONS Wheelbase Length (mm) Overall Dim - LxWxH (mm) 4 Wheel Track (mm) Min. Ground Clearance (mm) BODY Inner Dimensions - LxWxH Refrigeration Unit Insulation Thickness (mm) Flooring Door Access Stainless Steel Locking Bars Side Step Cargo Control Racks Tyes Centre Console, Overhead Locked Glove Box & Door Pockets Yes Centre Console, Overhead Locked Glove Box & Door Pockets Yes 2 x Powt 2 x USB 2 x Powt 2 x USB Exterior Mirrors 5 (2 x Power Adjustable & Heate 2 x Powt 2 x USB X Heate Yes Not on Chiller Body Yes 3200 GVM (kg) 5995 Max Payload - Chiller (kg) 2795 GCM (kg) 9495 Max Tow Rating (kg) DIMENSIONS Wheel Track (mm) 2800 Overall Dim - LxWxH (mm) 4 5400 x 1925 x 2230 Wheel Track (mm) 175 BODY Inner Dimensions - LxWxH 3430 x 2080 x 1920 Refrigeration Unit Thermo King RV380 Insulation Thickness (mm) 90 (Walls) 110 (Floor) Flooring Alloy with Side Protection Panel Door Access Stainless Steel Locking Bars Stide Step Yes (Retractable) Cargo Control Racks 3 x Stainless Steel "F" Track Row Tail Lift Activation Cordless Remote & Foot Control Tail Lift Activation Cordless Remote & Foot Control Tail Lift Roll Stop Yes WARRANTY Cab & Chassis 3 Year or 160,000km	Cruise Control	Yes
Storage Centre Console, Overhead Locker Glove Box & Door Pockets Cup Holders Power Outlets Exterior Mirrors Lane Departure Warning Reverse Camera Reverse Sensors 1 Kerb Weight - Chiller (kg) 2 GVM (kg) Max Payload - Chiller (kg) DIMENSIONS Wheelbase Length (mm) Overall Dim - LxWxH (mm) 4 Wheel Track (mm) Min. Ground Clearance (mm) BODY Inner Dimensions - LxWxH Refrigeration Unit Insulation Thickness (mm) Flooring Door Access Stainless Steel Locking Bars Side Step Cargo Control Racks A Yes Yes Yes Yes Yes Yes Yes Yes	MP5 / WMA / Radio Audio	Yes (Touch Screen)
Cup Holders Power Outlets Exterior Mirrors Lane Departure Warning Reverse Camera Reverse Sensors 1 Kerb Weight - Chiller (kg) GCM (kg) Max Payload - Chiller (kg) DIMENSIONS Wheelbase Length (mm) Overall Dim - LxWxH (mm) Min. Ground Clearance (mm) BODY Inner Dimensions - LxWxH Refrigeration Unit Insulation Thickness (mm) Flooring Door Access Door Locks Side Step Cargo Control Racks Til Lift Activation Cyes Ves Power Adjustable & Heate 1 2 x USB 5 (2 x Power Adjustable & Heate 2 x Port 2 x USB 5 (2 x Power Adjustable & Heate 2 x Port 2 x USB 5 (2 x Power Adjustable & Heate 2 x Port 2 x USB 5 (2 x Power Adjustable & Heate 2 x Port 2 x USB 5 (2 x Power Adjustable & Heate 2 x Port 2 x USB 5 (2 x Power Adjustable & Heate 2 x Port 2 x USB 5 (2 x Power Adjustable & Heate 2 x Port 2 x USB 5 (2 x Power Adjustable & Heate 4 x Sea 4 yes Floating Alloy on Chiller Body Yes Alano Yes Alano VEHICLE MASSES 3 x Stainless Steel (From) 175 BODY 1820 (Front) 1940 (Rear) 175 BODY Inner Dimensions - LxWxH 3430 x 2080 x 1920 Refrigeration Unit Thermo King RV380 Insulation Thickness (mm) 90 (Walls) 110 (Floor) Flooring Alloy with Side Protection Panel Door Access Stainless Steel Locking Bars Side Step Yes (Retractable) 3 x Stainless Steel "F" Track Row Tail Lift Activation Cordless Remote & Foot Control Tail Lift Activation Cordless Remote & Foot Control Tail Lift Roll Stop Yes WARRANTY Cab & Chassis 3 Year or 160,000km	Bluetooth Capability	Yes (Hands-free)
Power Outlets Exterior Mirrors For Society Service Adjustable & Heate Serv	Storage	Centre Console, Overhead Locker, Glove Box & Door Pockets
Exterior Mirrors Lane Departure Warning Reverse Camera Reverse Sensors 1 Reverse Alarm Yes VEHICLE MASSES 3 Kerb Weight - Chiller (kg) 2 GVM (kg) Max Payload - Chiller (kg) DIMENSIONS Wheelbase Length (mm) Overall Dim - LxWxH (mm) 4 Wheel Track (mm) Min. Ground Clearance (mm) BODY Inner Dimensions - LxWxH Refrigeration Unit Insulation Thickness (mm) Door Access Door Locks Stainless Steel Locking Bars Side Step Cargo Control Racks Tail Lift Tail Lift Activation Tail Lift Roll Stop WARRANTY Cab & Chassis Ato On Chiller & Heate Yes Not on Chiller Body Yes 1200 Alloy With Side Protection Yes Yes WARRANTY Cab & Chassis 3 Year or 160,000km	Cup Holders	Yes
Reverse Camera Reverse Sensors 1 Reverse Sensors 1 Reverse Alarm Reverse Alarm Yes VEHICLE MASSES 3 Kerb Weight - Chiller (kg) 2 GVM (kg) Max Payload - Chiller (kg) 3 GCM (kg) DIMENSIONS Wheelbase Length (mm) Overall Dim - LxWxH (mm) 4 Wheel Track (mm) BODY Inner Dimensions - LxWxH Refrigeration Unit Insulation Thickness (mm) Door Access Door Locks Stainless Steel Locking Bars Side Step Cargo Control Racks Tail Lift Tail Lift Activation Tail Lift Roll Stop WARRANTY Cab & Chassis Not on Chiller (kg) Yes Not on Chiller Body Yes 1200 S200 S200 S200 S200 S200 S200 S200	Power Outlets	2 x Port 2 x USB
Reverse Camera Reverse Sensors ¹ Reverse Alarm Yes VEHICLE MASSES ³ Kerb Weight - Chiller (kg) ² GVM (kg) Max Payload - Chiller (kg) GCM (kg) Max. Tow Rating (kg) DIMENSIONS Wheelbase Length (mm) Overall Dim - LxWxH (mm) ⁴ Wheel Track (mm) BODY Inner Dimensions - LxWxH Refrigeration Unit Insulation Thickness (mm) Door Access Door Locks Side Step Cargo Control Racks Tail Lift Tiel Inter Control Tail Lift Activation Tail Lift Roll Stop WARRANTY Cab & Chassis A200 S2795 3200 S4995 3200 S4995 3200 S4995 3400 2795 3200 2800 2795 3400 2810 2810 2810 2810 2810 2810 2810 2810 2810 2810 2810 381	Exterior Mirrors	5 (2 x Power Adjustable & Heated)
Reverse Camera Reverse Sensors 1 Reverse Alarm Yes VEHICLE MASSES 3 Kerb Weight - Chiller (kg) 2 GVM (kg) Max Payload - Chiller (kg) Max. Tow Rating (kg) DIMENSIONS Wheelbase Length (mm) Overall Dim - LxWxH (mm) 4 Wheel Track (mm) Min. Ground Clearance (mm) BODY Inner Dimensions - LxWxH Refrigeration Unit Insulation Thickness (mm) Door Access Door Locks Stainless Steel Locking Bars Side Step Cargo Control Racks Tail Lift Tiel Ith Roll Stop Air Deflector WARRANTY Cab & Chassis A200 S2795 3200 S400 2795 3200 S400 2795 3200 S400 2795 3200 S400 2795 3400 2800 2795 3400 2800	Lane Departure Warning	Yes
Reverse Alarm VEHICLE MASSES 3 Kerb Weight - Chiller (kg) 2 GVM (kg) 5995 Max Payload - Chiller (kg) 2795 GCM (kg) 9495 Max. Tow Rating (kg) 3500 DIMENSIONS Wheelbase Length (mm) 2800 Overall Dim - LxWxH (mm) 4 5400 x 1925 x 2230 Wheel Track (mm) 175 BODY Inner Dimensions - LxWxH 3430 x 2080 x 1920 Refrigeration Unit Thermo King RV380 Insulation Thickness (mm) 90 (Walls) 110 (Floor) Flooring Alloy with Side Protection Panel Door Access 1 x Single (LHS) & 1 x Double (Rea Side Step Yes (Retractable) 3 x Stainless Steel Locking Bars Side Step Yes (Retractable) 3 x Stainless Steel "F" Track Row Tail Lift 1 TC antilever (Optional) 1 Tail Lift Activation Cordless Remote & Foot Control Tail Lift Roll Stop Yes WARRANTY Cab & Chassis 3 Year or 160,000km		Yes
Reverse Alarm VEHICLE MASSES 3 Kerb Weight - Chiller (kg) 2 GVM (kg) 5995 Max Payload - Chiller (kg) 2795 GCM (kg) 9495 Max. Tow Rating (kg) 3500 DIMENSIONS Wheelbase Length (mm) 2800 Overall Dim - LxWxH (mm) 4 5400 x 1925 x 2230 Wheel Track (mm) 175 BODY Inner Dimensions - LxWxH 3430 x 2080 x 1920 Refrigeration Unit Thermo King RV380 Insulation Thickness (mm) 90 (Walls) 110 (Floor) Flooring Alloy with Side Protection Panel Door Access 1 x Single (LHS) & 1 x Double (Rea Side Step Yes (Retractable) 3 x Stainless Steel Locking Bars Side Step Yes (Retractable) 3 x Stainless Steel "F" Track Row Tail Lift 1 TC antilever (Optional) 1 Tail Lift Activation Cordless Remote & Foot Control Tail Lift Roll Stop Yes WARRANTY Cab & Chassis 3 Year or 160,000km	Reverse Sensors 1	Not on Chiller Body
Kerb Weight - Chiller (kg) 2 GVM (kg) 5995 Max Payload - Chiller (kg) 2795 GCM (kg) 9495 Max. Tow Rating (kg) 3500 DIMENSIONS Wheelbase Length (mm) 2800 Overall Dim - LxWxH (mm) 4 5400 x 1925 x 2230 Wheel Track (mm) 175 BODY Inner Dimensions - LxWxH 3430 x 2080 x 1920 Refrigeration Unit Thermo King RV380 Insulation Thickness (mm) 90 (Walls) 110 (Floor) Flooring Alloy with Side Protection Panel 1 x Single (LHS) & 1 x Double (Rea 5 Stainless Steel Locking Bars 5 Side Step Yes (Retractable) Cargo Control Racks 3 x Stainless Steel "F" Track Row 1 Track Control Tail Lift Activation Cordless Remote & Foot Control Tail Lift Roll Stop Yes WARRANTY Cab & Chassis 3 Year or 160,000km		
Kerb Weight - Chiller (kg) 2 GVM (kg) 5995 Max Payload - Chiller (kg) 2795 GCM (kg) 9495 Max. Tow Rating (kg) 3500 DIMENSIONS Wheelbase Length (mm) 2800 Overall Dim - LxWxH (mm) 4 5400 x 1925 x 2230 Wheel Track (mm) 175 BODY Inner Dimensions - LxWxH 3430 x 2080 x 1920 Refrigeration Unit Thermo King RV380 Insulation Thickness (mm) 90 (Walls) 110 (Floor) Flooring Alloy with Side Protection Panel 1 x Single (LHS) & 1 x Double (Rea 5 Stainless Steel Locking Bars 5 Side Step Yes (Retractable) Cargo Control Racks 3 x Stainless Steel "F" Track Row 1 Track Control Tail Lift Activation Cordless Remote & Foot Control Tail Lift Roll Stop Yes WARRANTY Cab & Chassis 3 Year or 160,000km		
GVM (kg) 5995 Max Payload - Chiller (kg) 2795 GCM (kg) 9495 Max. Tow Rating (kg) 3500 DIMENSIONS Wheelbase Length (mm) 2800 Overall Dim - LxWxH (mm) 5400 x 1925 x 2230 Wheel Track (mm) 1820 (Front) 1940 (Rear) Min. Ground Clearance (mm) 175 BODY Inner Dimensions - LxWxH 3430 x 2080 x 1920 Refrigeration Unit Thermo King RV380 Insulation Thickness (mm) 90 (Walls) 110 (Floor) Flooring Alloy with Side Protection Panel Door Access 1 x Single (LHS) & 1 x Double (Rea Door Locks Stainless Steel Locking Bars Side Step Yes (Retractable) Cargo Control Racks 3 x Stainless Steel "F" Track Row Tail Lift 1T Cantilever (Optional) Tail Lift Roll Stop Yes Air Deflector Yes WARRANTY 3 Year or 160,000km	Reverse Alarm	
Max Payload - Chiller (kg) GCM (kg) 9495 Max. Tow Rating (kg) 3500 DIMENSIONS Wheelbase Length (mm) Overall Dim - LxWxH (mm) 4 Wheel Track (mm) Min. Ground Clearance (mm) BODY Inner Dimensions - LxWxH Refrigeration Unit Insulation Thickness (mm) Flooring Alloy with Side Protection Panel Door Access 1 x Single (LHS) & 1 x Double (Rea Side Step Cargo Control Racks Tail Lift TI Cantilever (Optional) Tail Lift Roll Stop Air Deflector WARRANTY Cab & Chassis 3 Year or 160,000km	Reverse Alarm VEHICLE MASSES ³	Yes
GCM (kg) Max. Tow Rating (kg) DIMENSIONS Wheelbase Length (mm) Overall Dim - LxWxH (mm) Wheel Track (mm) Min. Ground Clearance (mm) BODY Inner Dimensions - LxWxH Refrigeration Unit Insulation Thickness (mm) Door Access Jay Stainless Steel Locking Bars Side Step Cargo Control Racks Tail Lift Til Cantilever (Optional) Tail Lift Roll Stop WARRANTY Cab & Chassis A800 2800 1820 Front) 1940 (Rear) 1820 (Front) 1940 (Rear) 1940 (Rear) 1940 (Rear) 1940 1940 (Rear) 1940 (Reverse Alarm VEHICLE MASSES ³ Kerb Weight - Chiller (kg) ²	Yes 3200
Max. Tow Rating (kg) DIMENSIONS Wheelbase Length (mm) Overall Dim - LxWxH (mm) Wheel Track (mm) Min. Ground Clearance (mm) BODY Inner Dimensions - LxWxH Refrigeration Unit Insulation Thickness (mm) Door Access Door Locks Stainless Steel Locking Bars Side Step Cargo Control Racks Tail Lift Tail Lift Activation Tail Lift Roll Stop WARRANTY Cab & Chassis Z800 2800 Alloy x 1925 x 2230 1820 (Front) 1940 (Rear) 175 B400 1820 (Front) 1940 (Rear) 1820 (Front) 1940 (Rear) 1820 (Front) 1940 (Rear) 1820 (Front) 1940 (Rear) 175 B410 (Flooring) Alloy with Side Protection Panel 1 x Single (LHS) & 1 x Double (Rear Steel Locking Bars) 3 x Stainless Steel Locking Bars Tail Lift Cordless Remote & Foot Control Yes WARRANTY Cab & Chassis 3 Year or 160,000km	Reverse Alarm VEHICLE MASSES ³ Kerb Weight - Chiller (kg) ² GVM (kg)	Yes 3200 5995
DIMENSIONS Wheelbase Length (mm) Overall Dim - LxWxH (mm) ⁴ S400 x 1925 x 2230 Wheel Track (mm) Min. Ground Clearance (mm) BODY Inner Dimensions - LxWxH Refrigeration Unit Insulation Thickness (mm) Plooring Alloy with Side Protection Panel Door Access 1 x Single (LHS) & 1 x Double (Rea Side Step Cargo Control Racks Tail Lift Tit Cantilever (Optional) Tail Lift Roll Stop Air Deflector WARRANTY Cab & Chassis Year or 160,000km	Reverse Alarm VEHICLE MASSES ³ Kerb Weight - Chiller (kg) ² GVM (kg) Max Payload - Chiller (kg)	Yes 3200 5995 2795
Wheelbase Length (mm) Overall Dim - LxWxH (mm) 4 Wheel Track (mm) Min. Ground Clearance (mm) BODY Inner Dimensions - LxWxH Refrigeration Unit Insulation Thickness (mm) Plooring Door Access Door Locks Stainless Steel Locking Bars Side Step Cargo Control Racks Tail Lift Titl Roll Stop Air Deflector WARRANTY Cab & Chassis P1820 (Front) 1940 (Rear) 1820 (Front) 1940 (Rear	Reverse Alarm VEHICLE MASSES ³ Kerb Weight - Chiller (kg) ² GVM (kg) Max Payload - Chiller (kg) GCM (kg)	Yes 3200 5995 2795 9495
Overall Dim - LxWxH (mm) 4 Wheel Track (mm) Min. Ground Clearance (mm) BODY Inner Dimensions - LxWxH Refrigeration Unit Insulation Thickness (mm) Door Access Door Locks Stainless Steel Locking Bars Side Step Cargo Control Racks Tail Lift Tit Cantilever (Optional) Tail Lift Roll Stop WARRANTY Cab & Chassis Alloo x 1920 (Front) 1940 (Rear) 175 1820 (Front) 1940 (Rear) 1940 (Foot) 194	Reverse Alarm VEHICLE MASSES ³ Kerb Weight - Chiller (kg) ² GVM (kg) Max Payload - Chiller (kg) GCM (kg) Max. Tow Rating (kg)	Yes 3200 5995 2795 9495
Wheel Track (mm) Min. Ground Clearance (mm) BODY Inner Dimensions - LxWxH Refrigeration Unit Insulation Thickness (mm) Plooring Alloy with Side Protection Panel Door Access I x Single (LHS) & 1 x Double (Rea Door Locks Stainless Steel Locking Bars Side Step Cargo Control Racks Tail Lift Track Row Tail Lift Activation Tail Lift Roll Stop Air Deflector WARRANTY Cab & Chassis Type (Front) 1940 (Rear) 175 1820 (Front) 1940 (Rear) 1820 (Foot) 194	Reverse Alarm VEHICLE MASSES ³ Kerb Weight - Chiller (kg) ² GVM (kg) Max Payload - Chiller (kg) GCM (kg) Max. Tow Rating (kg) DIMENSIONS	Yes 3200 5995 2795 9495 3500
Min. Ground Clearance (mm) BODY Inner Dimensions - LxWxH Refrigeration Unit Insulation Thickness (mm) Door Access Door Locks Stainless Steel Locking Bars Side Step Cargo Control Racks Tail Lift Tit Cantilever (Optional) Tail Lift Roll Stop Alloy With Side Protection Panel Alloy with Side Protection Panel Tx Single (LHS) & 1 x Double (Rea Tyes (Retractable) Tyes (Retractable) Tail Lift Toantilever (Optional) Tail Lift Activation Tail Lift Roll Stop Air Deflector WARRANTY Cab & Chassis Tyes Table Track Row Tyes	Reverse Alarm VEHICLE MASSES ³ Kerb Weight - Chiller (kg) ² GVM (kg) Max Payload - Chiller (kg) GCM (kg) Max. Tow Rating (kg) DIMENSIONS Wheelbase Length (mm)	Yes 3200 5995 2795 9495 3500
BODY Inner Dimensions - LxWXH Refrigeration Unit Thermo King RV380 Insulation Thickness (mm) Po (Walls) 110 (Floor) Flooring Door Access 1 x Single (LHS) & 1 x Double (Rea Door Locks Stainless Steel Locking Bars Side Step Yes (Retractable) Cargo Control Racks Tail Lift Trantilever (Optional) Tail Lift Activation Tail Lift Roll Stop Air Deflector WARRANTY Cab & Chassis 3 Year or 160,000km	Reverse Alarm VEHICLE MASSES ³ Kerb Weight - Chiller (kg) ² GVM (kg) Max Payload - Chiller (kg) GCM (kg) Max. Tow Rating (kg) DIMENSIONS Wheelbase Length (mm) Overall Dim - LxWxH (mm) ⁴	Yes 3200 5995 2795 9495 3500 2800 5400 x 1925 x 2230
Inner Dimensions - LxWxH Refrigeration Unit Refrigeration Unit Thermo King RV380 Insulation Thickness (mm) Po (Walls) 110 (Floor) Flooring Alloy with Side Protection Panel Door Access 1 x Single (LHS) & 1 x Double (Rea Door Locks Stainless Steel Locking Bars Side Step Yes (Retractable) Cargo Control Racks 3 x Stainless Steel "F" Track Row Tail Lift 1T Cantilever (Optional) Tail Lift Activation Cordless Remote & Foot Control Tail Lift Roll Stop Yes Air Deflector WARRANTY Cab & Chassis 3 Year or 160,000km	Reverse Alarm VEHICLE MASSES ³ Kerb Weight - Chiller (kg) ² GVM (kg) Max Payload - Chiller (kg) GCM (kg) Max. Tow Rating (kg) DIMENSIONS Wheelbase Length (mm) Overall Dim - LxWxH (mm) ⁴ Wheel Track (mm)	Yes 3200 5995 2795 9495 3500 2800 5400 x 1925 x 2230 1820 (Front) 1940 (Rear)
Refrigeration Unit Insulation Thickness (mm) Plooring Alloy with Side Protection Panel Door Access I x Single (LHS) & 1 x Double (Rea Door Locks Stainless Steel Locking Bars Side Step Yes (Retractable) Cargo Control Racks Tail Lift IT Cantilever (Optional) Tail Lift Roll Stop Air Deflector WARRANTY Cab & Chassis To (Walls) 110 (Floor) Alloy with Side Protection Panel I x Single (LHS) & 1 x Double (Rea Stainless Steel Locking Bars Stainless Steel "F" Track Row IT Cantilever (Optional) Tail Lift Activation Yes WARRANTY Tail & Garage Panel Thermo King RV380 To Ploor Tail (Floor) Tail Side Protection Panel Tail Cantilever (Optional) Tail Lift Roll Stop Yes Tail Deflector Tail Lift Roll Stop Tyes Tail Lift Roll Stop Tyes Tyes Thermo King RV380 Thermo King RV380 The Callon Panel Tail Cantilever (Optional) Tail Lift Activation Tail Lift Roll Stop Tyes Tyes Tyes Tyes Tyes Tyes Tyes Tyes	Reverse Alarm VEHICLE MASSES ³ Kerb Weight - Chiller (kg) ² GVM (kg) Max Payload - Chiller (kg) GCM (kg) Max. Tow Rating (kg) DIMENSIONS Wheelbase Length (mm) Overall Dim - LxWxH (mm) ⁴ Wheel Track (mm) Min. Ground Clearance (mm)	Yes 3200 5995 2795 9495 3500 2800 5400 x 1925 x 2230 1820 (Front) 1940 (Rear)
Insulation Thickness (mm) Flooring Alloy with Side Protection Panel Door Access 1 x Single (LHS) & 1 x Double (Rea Door Locks Stainless Steel Locking Bars Side Step Yes (Retractable) Cargo Control Racks 3 x Stainless Steel "F" Track Row Tail Lift 1T Cantilever (Optional) Tail Lift Activation Cordless Remote & Foot Control Tail Lift Roll Stop Yes WARRANTY Cab & Chassis 3 Year or 160,000km	Reverse Alarm VEHICLE MASSES ³ Kerb Weight - Chiller (kg) ² GVM (kg) Max Payload - Chiller (kg) GCM (kg) Max. Tow Rating (kg) DIMENSIONS Wheelbase Length (mm) Overall Dim - LxWxH (mm) ⁴ Wheel Track (mm) Min. Ground Clearance (mm) BODY	Yes 3200 5995 2795 9495 3500 2800 5400 x 1925 x 2230 1820 (Front) 1940 (Rear)
Flooring Alloy with Side Protection Panel Door Access 1 x Single (LHS) & 1 x Double (Rea Door Locks Stainless Steel Locking Bars Side Step Yes (Retractable) Cargo Control Racks 3 x Stainless Steel "F" Track Row Tail Lift 1T Cantilever (Optional) Tail Lift Activation Cordless Remote & Foot Control Tail Lift Roll Stop Yes Air Deflector WARRANTY Cab & Chassis 3 Year or 160,000km	Reverse Alarm VEHICLE MASSES ³ Kerb Weight - Chiller (kg) ² GVM (kg) Max Payload - Chiller (kg) GCM (kg) Max. Tow Rating (kg) DIMENSIONS Wheelbase Length (mm) Overall Dim - LxWxH (mm) ⁴ Wheel Track (mm) Min. Ground Clearance (mm) BODY Inner Dimensions - LxWxH	Yes 3200 5995 2795 9495 3500 2800 5400 x 1925 x 2230 1820 (Front) 1940 (Rear) 175 3430 x 2080 x 1920
Door Access 1 x Single (LHS) & 1 x Double (Read Door Locks Stainless Steel Locking Bars Side Step Yes (Retractable) Cargo Control Racks Tail Lift 1T Cantilever (Optional) Tail Lift Activation Tail Lift Roll Stop Air Deflector WARRANTY Cab & Chassis 1 x Single (LHS) & 1 x Double (Read Steel Read	Reverse Alarm VEHICLE MASSES ³ Kerb Weight - Chiller (kg) ² GVM (kg) Max Payload - Chiller (kg) GCM (kg) Max. Tow Rating (kg) DIMENSIONS Wheelbase Length (mm) Overall Dim - LxWxH (mm) ⁴ Wheel Track (mm) Min. Ground Clearance (mm) BODY Inner Dimensions - LxWxH Refrigeration Unit	Yes 3200 5995 2795 9495 3500 2800 5400 x 1925 x 2230 1820 (Front) 1940 (Rear) 175 3430 x 2080 x 1920 Thermo King RV380
Door Locks Stainless Steel Locking Bars Side Step Yes (Retractable) Cargo Control Racks 3 x Stainless Steel "F" Track Row Tail Lift 1T Cantilever (Optional) Tail Lift Activation Cordless Remote & Foot Control Tail Lift Roll Stop Yes Air Deflector Yes WARRANTY Cab & Chassis 3 Year or 160,000km	Reverse Alarm VEHICLE MASSES ³ Kerb Weight - Chiller (kg) ² GVM (kg) Max Payload - Chiller (kg) GCM (kg) Max. Tow Rating (kg) DIMENSIONS Wheelbase Length (mm) Overall Dim - LxWxH (mm) ⁴ Wheel Track (mm) Min. Ground Clearance (mm) BODY Inner Dimensions - LxWxH Refrigeration Unit Insulation Thickness (mm)	Yes 3200 5995 2795 9495 3500 2800 5400 x 1925 x 2230 1820 (Front) 1940 (Rear) 175 3430 x 2080 x 1920 Thermo King RV380 90 (Walls) 110 (Floor)
Side Step Yes (Retractable) Cargo Control Racks 3 x Stainless Steel "F" Track Row Tail Lift 1T Cantilever (Optional) Tail Lift Activation Cordless Remote & Foot Control Tail Lift Roll Stop Yes Air Deflector WARRANTY Cab & Chassis 3 Year or 160,000km	Reverse Alarm VEHICLE MASSES ³ Kerb Weight - Chiller (kg) ² GVM (kg) Max Payload - Chiller (kg) GCM (kg) Max. Tow Rating (kg) DIMENSIONS Wheelbase Length (mm) Overall Dim - LxWxH (mm) ⁴ Wheel Track (mm) Min. Ground Clearance (mm) BODY Inner Dimensions - LxWxH Refrigeration Unit Insulation Thickness (mm)	Yes 3200 5995 2795 9495 3500 2800 5400 x 1925 x 2230 1820 (Front) 1940 (Rear) 175 3430 x 2080 x 1920 Thermo King RV380 90 (Walls) 110 (Floor) Alloy with Side Protection Panels
Cargo Control Racks 3 x Stainless Steel "F" Track Row Tail Lift 1T Cantilever (Optional) Tail Lift Activation Cordless Remote & Foot Control Tail Lift Roll Stop Yes Air Deflector WARRANTY Cab & Chassis 3 Year or 160,000km	Reverse Alarm VEHICLE MASSES ³ Kerb Weight - Chiller (kg) ² GVM (kg) Max Payload - Chiller (kg) GCM (kg) Max. Tow Rating (kg) DIMENSIONS Wheelbase Length (mm) Overall Dim - LxWxH (mm) ⁴ Wheel Track (mm) Min. Ground Clearance (mm) BODY Inner Dimensions - LxWxH Refrigeration Unit Insulation Thickness (mm) Flooring Door Access	3200 5995 2795 9495 3500 2800 5400 x 1925 x 2230 1820 (Front) 1940 (Rear) 175 3430 x 2080 x 1920 Thermo King RV380 90 (Walls) 110 (Floor) Alloy with Side Protection Panels 1 x Single (LHS) & 1 x Double (Rear)
Tail Lift 1T Cantilever (Optional) Tail Lift Activation Cordless Remote & Foot Control Tail Lift Roll Stop Yes Air Deflector Yes WARRANTY Cab & Chassis 3 Year or 160,000km	Reverse Alarm VEHICLE MASSES ³ Kerb Weight - Chiller (kg) ² GVM (kg) Max Payload - Chiller (kg) GCM (kg) Max. Tow Rating (kg) DIMENSIONS Wheelbase Length (mm) Overall Dim - LxWxH (mm) ⁴ Wheel Track (mm) Min. Ground Clearance (mm) BODY Inner Dimensions - LxWxH Refrigeration Unit Insulation Thickness (mm) Flooring Door Access Door Locks	Yes 3200 5995 2795 9495 3500 2800 5400 x 1925 x 2230 1820 (Front) 1940 (Rear) 175 3430 x 2080 x 1920 Thermo King RV380 90 (Walls) 110 (Floor) Alloy with Side Protection Panels 1 x Single (LHS) & 1 x Double (Rear) Stainless Steel Locking Bars
Tail Lift Activation Cordless Remote & Foot Control Tail Lift Roll Stop Yes Air Deflector Yes WARRANTY Cab & Chassis 3 Year or 160,000km	Reverse Alarm VEHICLE MASSES ³ Kerb Weight - Chiller (kg) ² GVM (kg) Max Payload - Chiller (kg) GCM (kg) Max. Tow Rating (kg) DIMENSIONS Wheelbase Length (mm) Overall Dim - LxWxH (mm) ⁴ Wheel Track (mm) Min. Ground Clearance (mm) BODY Inner Dimensions - LxWxH Refrigeration Unit Insulation Thickness (mm) Flooring Door Access Door Locks Side Step	Yes 3200 5995 2795 9495 3500 2800 5400 x 1925 x 2230 1820 (Front) 1940 (Rear) 175 3430 x 2080 x 1920 Thermo King RV380 90 (Walls) 110 (Floor) Alloy with Side Protection Panels 1 x Single (LHS) & 1 x Double (Rear) Stainless Steel Locking Bars Yes (Retractable)
Tail Lift Roll Stop Yes Air Deflector Yes WARRANTY Cab & Chassis 3 Year or 160,000km	Reverse Alarm VEHICLE MASSES ³ Kerb Weight - Chiller (kg) ² GVM (kg) Max Payload - Chiller (kg) GCM (kg) Max. Tow Rating (kg) DIMENSIONS Wheelbase Length (mm) Overall Dim - LxWxH (mm) ⁴ Wheel Track (mm) Min. Ground Clearance (mm) BODY Inner Dimensions - LxWxH Refrigeration Unit Insulation Thickness (mm) Flooring Door Access Door Locks Side Step	Yes 3200 5995 2795 9495 3500 2800 5400 x 1925 x 2230 1820 (Front) 1940 (Rear) 175 3430 x 2080 x 1920 Thermo King RV380 90 (Walls) 110 (Floor) Alloy with Side Protection Panels 1 x Single (LHS) & 1 x Double (Rear) Stainless Steel Locking Bars Yes (Retractable) 3 x Stainless Steel "F" Track Rows
Air Deflector Yes WARRANTY Cab & Chassis 3 Year or 160,000km	Reverse Alarm VEHICLE MASSES ³ Kerb Weight - Chiller (kg) ² GVM (kg) Max Payload - Chiller (kg) GCM (kg) Max. Tow Rating (kg) DIMENSIONS Wheelbase Length (mm) Overall Dim - LxWxH (mm) ⁴ Wheel Track (mm) Min. Ground Clearance (mm) BODY Inner Dimensions - LxWxH Refrigeration Unit Insulation Thickness (mm) Flooring Door Access Door Locks Side Step Cargo Control Racks	Yes 3200 5995 2795 9495 3500 2800 5400 x 1925 x 2230 1820 (Front) 1940 (Rear) 175 3430 x 2080 x 1920 Thermo King RV380 90 (Walls) 110 (Floor) Alloy with Side Protection Panels 1 x Single (LHS) & 1 x Double (Rear) Stainless Steel Locking Bars Yes (Retractable) 3 x Stainless Steel "F" Track Rows
WARRANTY Cab & Chassis 3 Year or 160,000km	Reverse Alarm VEHICLE MASSES ³ Kerb Weight - Chiller (kg) ² GVM (kg) Max Payload - Chiller (kg) GCM (kg) Max. Tow Rating (kg) DIMENSIONS Wheelbase Length (mm) Overall Dim - LxWxH (mm) ⁴ Wheel Track (mm) Min. Ground Clearance (mm) BODY Inner Dimensions - LxWxH Refrigeration Unit Insulation Thickness (mm) Flooring Door Access Door Locks Side Step Cargo Control Racks Tail Lift	Yes 3200 5995 2795 9495 3500 2800 5400 x 1925 x 2230 1820 (Front) 1940 (Rear) 175 3430 x 2080 x 1920 Thermo King RV380 90 (Walls) 110 (Floor) Alloy with Side Protection Panels 1 x Single (LHS) & 1 x Double (Rear) Stainless Steel Locking Bars Yes (Retractable) 3 x Stainless Steel "F" Track Rows
Cab & Chassis 3 Year or 160,000km	Reverse Alarm VEHICLE MASSES ³ Kerb Weight - Chiller (kg) ² GVM (kg) Max Payload - Chiller (kg) GCM (kg) Max. Tow Rating (kg) DIMENSIONS Wheelbase Length (mm) Overall Dim - LxWxH (mm) ⁴ Wheel Track (mm) Min. Ground Clearance (mm) BODY Inner Dimensions - LxWxH Refrigeration Unit Insulation Thickness (mm) Flooring Door Access Door Locks Side Step Cargo Control Racks Tail Lift Tail Lift Activation	Yes 3200 5995 2795 9495 3500 2800 5400 x 1925 x 2230 1820 (Front) 1940 (Rear) 175 3430 x 2080 x 1920 Thermo King RV380 90 (Walls) 110 (Floor) Alloy with Side Protection Panels 1 x Single (LHS) & 1 x Double (Rear) Stainless Steel Locking Bars Yes (Retractable) 3 x Stainless Steel "F" Track Rows 1T Cantilever (Optional) Cordless Remote & Foot Controls
	Reverse Alarm VEHICLE MASSES ³ Kerb Weight - Chiller (kg) ² GVM (kg) Max Payload - Chiller (kg) GCM (kg) Max. Tow Rating (kg) DIMENSIONS Wheelbase Length (mm) Overall Dim - LxWxH (mm) ⁴ Wheel Track (mm) Min. Ground Clearance (mm) BODY Inner Dimensions - LxWxH Refrigeration Unit Insulation Thickness (mm) Flooring Door Access Door Locks Side Step Cargo Control Racks Tail Lift Activation Tail Lift Roll Stop	Yes 3200 5995 2795 9495 3500 2800 5400 x 1925 x 2230 1820 (Front) 1940 (Rear) 175 3430 x 2080 x 1920 Thermo King RV380 90 (Walls) 110 (Floor) Alloy with Side Protection Panels 1 x Single (LHS) & 1 x Double (Rear) Stainless Steel Locking Bars Yes (Retractable) 3 x Stainless Steel "F" Track Rows 1T Cantilever (Optional) Cordless Remote & Foot Controls Yes
Job Ready [™] Body 1 Year or 20,000km	Reverse Alarm VEHICLE MASSES ³ Kerb Weight - Chiller (kg) ² GVM (kg) Max Payload - Chiller (kg) GCM (kg) Max. Tow Rating (kg) DIMENSIONS Wheelbase Length (mm) Overall Dim - LxWxH (mm) ⁴ Wheel Track (mm) Min. Ground Clearance (mm) BODY Inner Dimensions - LxWxH Refrigeration Unit Insulation Thickness (mm) Flooring Door Access Door Locks Side Step Cargo Control Racks Tail Lift Activation Tail Lift Roll Stop Air Deflector	Yes 3200 5995 2795 9495 3500 2800 5400 x 1925 x 2230 1820 (Front) 1940 (Rear) 175 3430 x 2080 x 1920 Thermo King RV380 90 (Walls) 110 (Floor) Alloy with Side Protection Panels 1 x Single (LHS) & 1 x Double (Rear) Stainless Steel Locking Bars Yes (Retractable) 3 x Stainless Steel "F" Track Rows 1T Cantilever (Optional) Cordless Remote & Foot Controls Yes
	Reverse Alarm VEHICLE MASSES ³ Kerb Weight - Chiller (kg) ² GVM (kg) Max Payload - Chiller (kg) GCM (kg) Max. Tow Rating (kg) DIMENSIONS Wheelbase Length (mm) Overall Dim - LxWxH (mm) ⁴ Wheel Track (mm) Min. Ground Clearance (mm) BODY Inner Dimensions - LxWxH Refrigeration Unit Insulation Thickness (mm) Flooring Door Access Door Locks Side Step Cargo Control Racks Tail Lift Tail Lift Roll Stop Air Deflector WARRANTY	Yes 3200 5995 2795 9495 3500 2800 5400 x 1925 x 2230 1820 (Front) 1940 (Rear) 175 3430 x 2080 x 1920 Thermo King RV380 90 (Walls) 110 (Floor) Alloy with Side Protection Panels 1 x Single (LHS) & 1 x Double (Rear) Stainless Steel Locking Bars Yes (Retractable) 3 x Stainless Steel "F" Track Rows 1T Cantilever (Optional) Cordless Remote & Foot Controls Yes Yes
OPTIONAL FEATURES	Reverse Alarm VEHICLE MASSES ³ Kerb Weight - Chiller (kg) ² GVM (kg) Max Payload - Chiller (kg) GCM (kg) Max. Tow Rating (kg) DIMENSIONS Wheelbase Length (mm) Overall Dim - LxWxH (mm) ⁴ Wheel Track (mm) Min. Ground Clearance (mm) BODY Inner Dimensions - LxWxH Refrigeration Unit Insulation Thickness (mm) Flooring Door Access Door Locks Side Step Cargo Control Racks Tail Lift Tail Lift Activation Tail Lift Roll Stop Air Deflector WARRANTY Cab & Chassis	Yes 3200 5995 2795 9495 3500 2800 5400 x 1925 x 2230 1820 (Front) 1940 (Rear) 175 3430 x 2080 x 1920 Thermo King RV380 90 (Walls) 110 (Floor) Alloy with Side Protection Panels 1 x Single (LHS) & 1 x Double (Rear) Stainless Steel Locking Bars Yes (Retractable) 3 x Stainless Steel "F" Track Rows 1T Cantilever (Optional) Cordless Remote & Foot Controls Yes Yes 3 Year or 160,000km

1 Reverse sensors included on specific Job Ready [™] models only. Refer your local Foton dealer for details.
2 Kerb weights are approximate only and include the vehicle with 80L of fuel, spare wheel & tool kit.
3 Vehicle load ratings & axle capacities may be limited by local laws. Always refer to NZTA when confirming load restrictions & license class requirements.
4 Overall dimensions taken from original Cab Chassis

Foton Trucks are distributed in New Zealand by Foton Truck NZ (Anglesea Vehicle Distributors Ltd). All effort has been made to ensure the information contained in this brochure was correct at time of printing. Foton Truck NZ reserves the right to alter any details of the specifications & equipment without notice. Foton Truck NZ, in so far as it is permitted by law to do so, shall not be liable in any way as a result of any reliance placed by any person on anything contained in this brochure. You should therefore check with your authorised Foton Truck Dealer at the time of ordering your motor vehicle to ensure that colour, specifications, equipment, design features & options are available for the vehicle you are ordering.

Part No. FNZ-SPEC-1065R Issue Date: 05/09/2023