

FOTON AUMARK S

NEW ZEALAND'S ONLY LIGHT DUTY TRUCK POWERED BY CUMMINS

JOB READY™ RANGE



**BJ1088
SCAFF PACK**



FOTON DNA:



FOTON

| MAKE & MODEL | |
|--------------------------------|---|
| Vehicle Make | FOTON |
| Model & Variant | Aumark S - BJ1088 Scaff Pack |
| ENGINE | |
| Supplier Version Displace. | CUMMINS ISF 3.8L |
| Turbocharger | Yes (with Intercooler) |
| Rated Power (kW) | 115 @ 2600rpm |
| Rated Torque (Nm) | 500 @ 1200-1900rpm |
| Emission Standard | Euro 5 |
| Emission Control | AdBlue |
| FUEL | |
| Supplier System | BOSCH Common Rail Direct Injection |
| Tank Capacity | 160L |
| Tank Material | Alloy |
| ELECTRICAL | |
| System Voltage (V) | 24 |
| Batteries (V) | 2 x 12 (100Ah) |
| CAN Bus Technology | Yes |
| EBP (Fuel Saving Switch) | Yes |
| LIGHTING | |
| Headlamp Type | Integrated Halogen (LED DRL) |
| Fog Lamps | Yes (Front & Rear) |
| Roof Clearance Lights | Yes (LED) |
| Step Lighting | Yes (Driver & Passenger) |
| Daytime Running Lights | Yes (LED) |
| Height Adjustable Headlights | Yes |
| TRANSMISSION | |
| Supplier Version | ZF Ecolite 6S500 (MT) |
| Gears | 6 Speed |
| Drive Type | 4 x 2 |
| PTO Provision | Yes (LHS of Gearbox) |
| Gear Ratios (:1) | 1 st : 6.198 2 nd : 3.287 3 rd : 2.025 4 th : 1.371 5 th : 1.000 6 th : 0.780 Rev: 5.681 |
| CLUTCH | |
| Operation | Single Disc, Dry Diaphragm Spring |
| System | Air Boost |
| Diameter (mm) | 362 |
| CHASSIS | |
| Type | Longitudinal Beam High Strength Steel |
| Side Rail Dimensions | 214 x 65 x 5 |
| STEERING | |
| Operation | Recirculating Ball Steering Gear |
| Type | Power Assisted |
| Turning Radius (m) | 7.75 |
| Steering Column | 2-Way Adjustable |
| Steering Wheel Controls | Audio / Bluetooth / Cruise Control |
| SUSPENSION | |
| Suspension Type - Front | Multi Leaf Spring |
| - Rear | Multi Leaf Spring with Helper Spring |
| Stabiliser Bar | Yes (Front & Rear) |
| Shock Absorbers | Yes (Double Acting) |
| BRAKES | |
| Supplier System | WABCO Air Brake |
| Brake Type | Disc (Front & Rear) |
| Anti-Lock Brakes (ABS) | Yes |
| Electronic Brake Dist. (EBD) | Yes |
| Traction Control (ASR) | Yes |
| Electronic Stabilisers (ESP) | Yes |
| Hill Start Assist (HSA) | Yes |
| Exhaust Brake | Yes |

| Parking Brake | Air Activated (Rear) | |
|---------------------------------------|---|-----------|
| Parkbrake Alarm | Yes | |
| Air Tank Material | Alloy (x 2) | |
| AXLES ¹ | | |
| Axle Type - Front | Forged & Stamped I-Beam | |
| - Rear | Stamped & Welded Banjo | |
| Axle Max Capacities (kg) | 3100 (Front) 6600 (Rear) | |
| Rear Axle Ratios | 4.3 : 1 | |
| WHEEL & TYRE | | |
| Wheel Size (Inches) | 6.00 x 17.5 | |
| Tyre Size | 215/75 R17.5 | |
| No. of Studs | 6 | |
| Tyre Pressure Monitoring | Yes | |
| INTERIOR & CAB | | |
| Cab Type | Single Cab Forward Control Tilt (40°) | |
| Cab Structure | ECE-R29 Cab Strength Approved | |
| Door Impact Beam | Yes | |
| Seating Capacity | 3 | |
| Heating & Air Conditioning | Yes | |
| Steering Wheel | Collapsible/Adjustable (Telescopic & Tilt) | |
| Central Locking | Yes (Remote) | |
| Power Windows | Yes | |
| Height Adjustable Seatbelt | Driver Only | |
| Cruise Control | Yes | |
| MP5 / WMA / Radio Audio | Yes (Touch Screen) | |
| Bluetooth Capability | Yes (Hands-free) | |
| Storage | Centre Console, Overhead Locker, Glove Box & Door Pockets | |
| Cup Holders | 4 | |
| Power Outlets | 2 | |
| Exterior Mirrors | 5 (2 x Power Adjustable & Heated) | |
| Lane Departure Warning | Yes | |
| VEHICLE MASSES ¹ | | |
| | (Class 1) | (Class 2) |
| GVM (kg) | 5995 | 8995 |
| GCM (kg) | 5995 | 12495 |
| Max Payload - Scaff Pack | 1995 | 4995 |
| Kerb Weight - Scaff Pack ⁴ | 4000 | |
| Max. Tow Rating (kg) | 3500 | |
| DIMENSIONS | | |
| Wheelbase (mm) | 3800 | |
| Overall Dim - LxWxH (mm) ² | 6953 x 2200 x 2350 | |
| Wheel Track (mm) | 1762 (Front) 1615 (Rear) | |
| Min. Ground Clearance (mm) | 160 | |
| BODY | | |
| Inner Dim - LxWxH | 5140 x 2200 x 400 | |
| Body Type | Scaff Pack Tray | |
| Deck Height (from floor) | 1030 | |
| Tray Floor | 3mm Steel | |
| Strop Holes | Yes (6 per side) | |
| Tie down Rails | Yes (Certified) | |
| Side Rail Caps | Yes (Stainless Steel) | |
| Headboard | Diamond Mesh with Stainless Plate | |
| Steel Toolbox | Yes (Underbody LHS) | |
| Steel Side Steps | Yes (All 4 Corners) | |
| Reverse Alarm & Sensors ³ | Yes | |
| WARRANTY | | |
| Cab and Chassis | 3 Years or 160,000 km | |
| Job Ready™ Body | 1 Year or 20,000 km | |
| OPTIONAL FEATURES | | |
| Metallic Paint | Optional | |

¹ Vehicle load ratings & axle capacities may be limited by local laws. Always refer to NZTA when confirming load restrictions & license class requirements.

² Overall dimensions taken from original Cab Chassis

³ Reverse sensors included on specific Job Ready™ models only. Refer your local Foton dealer for details.

⁴ Kerb weights are approximate only and include the vehicle with 80L of fuel, spare wheel & tool kit.

Foton Trucks are distributed in New Zealand by Foton Truck NZ (Anglesea Vehicle Distributors Ltd). All effort has been made to ensure the information contained in this brochure was correct at time of printing. Foton Truck NZ reserves the right to alter any details of the specifications & equipment without notice. Foton Truck NZ, in so far as it is permitted by law to do so, shall not be liable in any way as a result of any reliance placed by any person on anything contained in this brochure. You should therefore check with your authorised Foton Truck Dealer at the time of ordering your motor vehicle to ensure that colour, specifications, equipment, design features & options are available for the vehicle you are ordering.